

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9309	9	71-9309	USA/9309/B(U)F-96	1 OF	8

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- |   |   |
|---|---|
| a. ISSUED TO ( <i>Name and Address</i> )<br>Global Nuclear Fuel - Americas, LLC<br>P.O. Box 780<br>Wilmington, NC 28402 | b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION<br>Global Nuclear Fuel - Americas, LLC, application dated<br>May 5, 2009, as supplemented. |
|---|---|

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

(a) Packaging

(1) Model No.: RAJ-II

(2) Description

The RAJ-II package is a rectangular box that is 742 mm (29.21 in) high by 720 mm (28.35 in) wide by 5,068 mm (199.53 in) long to transport a maximum of two Boiling Water Reactor (BWR) fuel assemblies or individual rods that meet the ASTM C996-96 standard of enriched commercial grade uranium, enriched reprocessed uranium, uranium oxide generic pressurized water reactor (PWR) or uranium carbide loose fuel rods in a 5 inch diameter stainless steel pipe.

It is comprised of one inner container and one outer container both made of stainless steel. The inner container is comprised of a double-wall stainless steel sheet structure with alumina silicate thermal insulator filling the gap between the two walls to reduce the flow of the heat into the contents in the event of a fire. Foam polyethylene cushioning material is placed on the inside of the inner container for protection of the fuel assembly. The outer container is comprised of a stainless steel angular framework covered with stainless steel plates. Inner container clamps are installed inside the outer container with a vibro-isolating device between to alleviate vibration occurring during transportation. Wood and honeycomb resin impregnated kraft paper are placed as shock absorbers to reduce shock in the event of a drop of the package. The fuel rod clad and ceramic nature of the fuel pellets provide primary containment of the radioactive material.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9309	9	71-9309	USA/9309/B(U)F-96	2 OF	8

5.(a)(2) continued

The approximate dimensions and weights of the package are as follows:

Maximum gross shipping weight	1,614 kg (3,558 lbs)
Maximum weight of inner container	308 kg (679 lbs)
Maximum weight of outer container	622 kg (1,371 lbs)
Maximum weight of packaging	930 kg (2,050 lbs)
Dimensions of inner container	
Length	4,686 mm (184.49 in)
Width	459 mm (18.07 in)
Height	286 mm (11.26 in)
Dimensions of outer container	
Length	5,068 mm (199.53 in)
Width	720 mm (28.35 in)
Height	742 mm (29.21 in)

(3) Drawings

This packaging is constructed in accordance with the Global Nuclear Fuel (GNF) Drawing Nos.:

Outer Container Drawings

105E3737, Rev. 6  
105E3738, Sheets 1 and 2, Rev. 8  
105E3738, Sheet 3, Rev. 7  
105E3739, Rev. 4  
105E3740, Rev. 4  
105E3741, Rev. 1  
105E3742, Rev. 3  
105E3743, Rev. 5  
105E3744, Rev. 6

Inner Container Drawings

105E3745, Rev. 8  
105E3746, Rev. 1  
105E3747, Rev. 4  
105E3748, Rev. 2  
105E3749, Rev. 6

Contents Containers

105E3773, Rev. 1  
0028B98, Rev. 1

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER 9309	b. REVISION NUMBER 9	c. DOCKET NUMBER 71-9309	d. PACKAGE IDENTIFICATION NUMBER USA/9309/B(U)F-96	PAGE 3	PAGES OF 8
----------------------------------	-------------------------	-----------------------------	---	-----------	---------------

5. continued

(b) Contents

(1) Type and form of material

Enriched commercial grade uranium or enriched reprocessed uranium, as defined in ASTM C996-96, uranium oxide or uranium carbide fuel rods enriched to no more than 5.0 weight percent in the U-235 isotope, with limits specified in Table 1 and Table 2 below.

Table 1: Maximum weight of uranium dioxide pellets per fuel assembly

Type 8x8 fuel assembly	Type 9x9 fuel assembly	Type 10x10 fuel assembly
235 kg	240 kg	275 kg

Table 2: Maximum Authorized Concentrations

Isotope	Maximum content
U-232	$2.00 \times 10^{-9}$ g/gU
U-234	$2.00 \times 10^{-3}$ g/gU
U-235	$5.00 \times 10^{-2}$ g/gU
U-236	$2.50 \times 10^{-2}$ g/gU
Np-237	$1.66 \times 10^{-6}$ g/gU
Pu-238	$6.20 \times 10^{-11}$ g/gU
Pu-239	$3.04 \times 10^{-9}$ g/gU
Pu-240	$3.04 \times 10^{-9}$ g/gU
Gamma Emitters	$5.18 \times 10^5$ MeV - Bq/kgU

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER 9309	b. REVISION NUMBER 9	c. DOCKET NUMBER 71-9309	d. PACKAGE IDENTIFICATION NUMBER USA/9309/B(U)F-96	PAGE 4	PAGES OF 8
----------------------------------	-------------------------	-----------------------------	---	-----------	---------------

5.(b)(1) continued

- (i) 8 x 8 fuel assemblies comprised of 60 to 64 rods in a square array with a maximum active fuel rod length of 381 cm. The maximum pellet diameter, minimum clad thickness, rod pitch, water rod specifications, and poison rod specification are in accordance with Table 3 below.
- (ii) 9 x 9 fuel assemblies comprised of 72 to 81 rods in a square array with a maximum active fuel rod length of 381 cm. The maximum pellet diameter, minimum clad thickness, rod pitch, water rod specifications, and poison rod specification are in accordance with Table 3 below.
- (iii) 10 x 10 fuel assemblies comprised of 91 to 100 rods in a square array with a maximum active fuel rod length of 385 cm. The maximum pellet diameter, minimum clad thickness, rod pitch, water rod specifications, and poison rod specification are in accordance with Table 3 below.
- (iv) Oxide fuel rods configured loose, in a 5 inch diameter schedule 40 stainless steel pipe/protective case or strapped together. When fuel rods are placed in polyethylene sleeves, each polyethylene sleeve shall not exceed 0.0152 cm in thickness. The maximum pellet diameter, minimum clad thickness, and rod specifications are in accordance with Table 4 below.
- (v) Uranium carbide or generic PWR uranium oxide fuel rods configured loose, in a 5 inch diameter schedule 40 stainless steel pipe. When fuel rods are placed in polyethylene sleeves, each polyethylene sleeve shall not exceed 0.0152 cm in thickness. The maximum pellet diameter, minimum clad thickness, and rod specifications are in accordance with Table 4 below.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9309	9	71-9309	USA/9309/B(U)F-96	5 OF	8

5.(b)(1) continued

Table 3: Fuel Assembly Parameters

Parameter	Units	Type	Type	Type	Type
Fuel Assembly Type	Rods	8x8	9x9	FANP 10x10	GNF 10x10
UO <sub>2</sub> Density		≤ 98% Theoretical	≤ 98% Theoretical	≤ 98% Theoretical	≤ 98% Theoretical
Number of water rods (See Condition 8)	#	0, 2x2	0, 2-2x2 off-center diagonal, 3x3	0, 2-2x2 off-center diagonal, 3x3	0, 2-2x2 off-center diagonal, 3x3
Number of fuel rods	#	60 - 64	72 - 81	91 - 100	91 - 100
Fuel Rod OD	cm	≥ 1.176	≥ 1.093	≥ 1.000	≥ 1.010
Fuel Pellet OD	cm	≤ 1.05	≤ 0.96	≤ 0.895	≤ 0.895
Cladding Type		Zirconium Alloy	Zirconium Alloy	Zirconium Alloy	Zirconium Alloy
Cladding ID	cm	≤ 1.10	≤ 1.02	≤ 0.933	≤ 0.934
Cladding Thickness	cm	≥ 0.038	≥ 0.036	≥ 0.033	≥ 0.038
Active fuel length	cm	≤ 381	≤ 381	≤ 385	≤ 385
Nominal Fuel Rod Pitch	cm	1.63	≤ 1.45	≤ 1.30	1.30
U-235 Pellet Enrichment	wt%	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5.0
Maximum Lattice Average Enrichment	wt%	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5.0
Channel Thickness <sup>a</sup>	cm	0.17 - 0.3048	0.17 - 0.3048	0.17 - 0.3048	0.17 - 0.3048
Partial Length Fuel Rods (1/3 through 2/3 normal length)	Max #	None	12	14	14
Gadolinia Requirements Lattice Average Enrichment <sup>b</sup>	# @ wt% Gd <sub>2</sub> O <sub>3</sub>	7 @ 2 wt % 6 @ 2 wt % 6 @ 2 wt % 6 @ 2 wt % 4 @ 2 wt % 4 @ 2 wt % 4 @ 2 wt % 4 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % None None None	10 @ 2 wt % 8 @ 2 wt % 8 @ 2 wt % 8 @ 2 wt % 6 @ 2 wt % 6 @ 2 wt % 4 @ 2 wt % 4 @ 2 wt % 4 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % None None None	12 @ 2 wt % 12 @ 2 wt % 10 @ 2 wt % 9 @ 2 wt % 8 @ 2 wt % 8 @ 2 wt % 6 @ 2 wt % 6 @ 2 wt % 6 @ 2 wt % 4 @ 2 wt % 4 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % None	12 @ 2 wt % 12 @ 2 wt % 10 @ 2 wt % 9 @ 2 wt % 8 @ 2 wt % 8 @ 2 wt % 6 @ 2 wt % 6 @ 2 wt % 6 @ 2 wt % 4 @ 2 wt % 4 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % 2 @ 2 wt % None
Polyethylene Equivalent Mass (Maximum per Assembly) <sup>c</sup>	kg	11	11	10.2	10.2

- a. Transport with or without channels is acceptable
- b. Required gadolinia rods must be distributed symmetrically about the major diagonal
- c. Polyethylene equivalent mass calculation (refer to 6.3.2.2 of the application)

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER <b>9309</b>	b. REVISION NUMBER <b>9</b>	c. DOCKET NUMBER <b>71-9309</b>	d. PACKAGE IDENTIFICATION NUMBER <b>USA/9309/B(U)F-96</b>	PAGE <b>6</b>	PAGES <b>OF 8</b>
---	--------------------------------	------------------------------------	--	------------------	----------------------

5.(b)(1) continued

Table 4: Fuel Rod Parameters

Parameter	Units	Type					
		8x8 <sup>(1)</sup> (UO <sub>2</sub> )	9x9 <sup>(1)</sup> (UO <sub>2</sub> )	10x10 <sup>(1)</sup> (UO <sub>2</sub> )	CANDU-14 (UC)	CANDU-25 (UC)	Generic PWR (UO <sub>2</sub> )
Fuel Assembly Type							
UO <sub>2</sub> or UC Fuel Density		<98% theoretical	<98% theoretical	<98% theoretical	<98% theoretical	<98% theoretical	<98% theoretical
Fuel rod OD	cm	≥1.10	≥1.02	≥1.00	≥1.340	≥0.996	≥1.118
Fuel Pellet OD	cm	≤1.05	≤0.96	≤0.90	≤1.254	≤0.950	≤0.98
Cladding Type		Zirc. Alloy	Zirc. Alloy	Zirc. Alloy	Zirc. Alloy or SS	Zirc. Alloy or SS	Zirc. Alloy or SS
Cladding ID	cm	≤1.10	≤1.02	≤1.00	≤1.267	≤0.951	≤1.004
Cladding Thickness	cm	≥0.038	≥0.036	≥0.038	≥0.033	≥0.033	≥0.033
Active fuel Length	cm	≤381	≤381	≤385	≤47.752	≤40.013	≤450
Maximum U-235 Pellet Enrichment	wt. %	≤5.0	≤5.0	≤5.0	≤5.0	≤5.0	≤5.0
Maximum Average fuel rod Enrichment	wt. %	≤5.0	≤5.0	≤5.0	≤5.0	≤5.0	≤5.0
<b>Loose Rod Configuration</b>							
Freely Loose		≤25	≤25	≤25	N/A	N/A	N/A
Packed in 5" SS Pipe or Protective Case <sup>(3)</sup>		≤22	≤26	≤30	≤74 <sup>(2)</sup>	≤130 <sup>(2)</sup>	≤105 <sup>(2)</sup>
Strapped Together		≤25	≤25	≤25	N/A	N/A	N/A

<sup>(1)</sup> Previous analysis (Ref. 1) based on most conservative loose rod configuration (i.e., no credit taken for 5" SS pipe)

<sup>(2)</sup> Including partial rods (in reality, apply dense packing of congruent rods in the pipe) and only in 5" SS pipes

<sup>(3)</sup> Protective case consists of SS box with lid

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER 9309	b. REVISION NUMBER 9	c. DOCKET NUMBER 71-9309	d. PACKAGE IDENTIFICATION NUMBER USA/9309/B(U)F-96	PAGE 7	PAGES OF 8
----------------------------------	-------------------------	-----------------------------	---	-----------	---------------

5.(b)(2) Maximum quantity of material per package

Total weight of payload contents (fuel assemblies, or fuel rods and rod shipping containers) not to exceed 684 kg (1508 pounds).

- (i) For the contents described in 5(b)(1)(i), 5(b)(1)(ii), and 5(b)(1)(iii): two fuel assemblies.
- (ii) For the contents described in 5(b)(1)(iv) and 5(b)(1)(v): allowable number of fuel rods per compartment (2 compartments per package).

- (c) Criticality Safety Index, except for contents described in 5(b)(1)(v) and limited in 5(b)(2)(ii) 1.0
- Criticality Safety Index for contents described in 5(b)(1)(v) and limited in 5(b)(2)(ii) 2.1

6. In addition to the requirements of Subpart G of 10 CFR Part 71:

- (a) The package shall be prepared for shipment and operated in accordance with the Package Operations of Chapter 7 of the application.
- (b) The packaging must meet the Acceptance Tests and Maintenance Program of Chapter 8 of the application.
- (c) Prior to each shipment, the stainless steel components of the packaging must be visually inspected. Packages in which stainless steel components show pitting corrosion, cracking, or pinholes are not authorized for transport.
- (d) If wrapping is used on the unirradiated fuel assemblies, the ends must be assured to be open during the shipment in the package.

7. Cluster separators are optional and may be comprised of polyethylene or other plastics. Polyethylene or plastic mass limits shall be determined in accordance with Section 6.3.2.2 (Material Specifications) of the application.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9309	9	71-9309	USA/9309/B(U)F-96	8 OF	8

8. Water rods are limited as shown in Table 3 above.

For 8 x 8 fuel assembly designs, there can be either 0 or 1 water rod, and the water rod location occupies a space equivalent to 2 x 2 fuel rods. This is designated as 0, 2 x 2 in the table.

For 9 x 9 and 10 x 10 fuel assembly designs, there can be either 0, 1, or 2 water rods in the assembly, and the water rod location occupies a space equivalent to (a) two 2 x 2 fuel rod equivalent spaces on a diagonal at the center of the assembly, or (b) one 3 x 3 fuel rod equivalent space (9 fuel rods space) in the center of the assembly. These configurations are designated as 0, 2 - 2x2 off-center diagonal, 3x3 in the table.

9. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.

10. Transport by air of fissile material is not authorized.

11. Revision No. 7 of this certificate, amended to reference Drawing Nos.: 105E3738, Sheets 1 and 2, Rev. 8; 105E3743, Rev. 5; and 105E3744, Rev. 6; as listed in Condition 5(a)(3), may be used until August 31, 2010.

12. Expiration date: November 30, 2014.

REFERENCES

Global Nuclear Fuel - Americas, LLC, application dated May 5, 2009.

Supplement dated: August 24, 2009.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION



Eric Benner, Chief  
Licensing Branch  
Division of Spent Fuel Storage and Transportation  
Office of Nuclear Material Safety  
and Safeguards

Date: August 25, 2009



UNITED STATES  
NUCLEAR REGULATORY COMMISSION  
WASHINGTON, D.C. 20555-0001

SAFETY EVALUATION REPORT

Docket No. 71-9309  
Model No. RAJ-II Package  
Certificate of Compliance No. 9309  
Revision No. 9

**SUMMARY**

By application dated August 24, 2009, Global Nuclear Fuel – Americas, LLC (GNF-A), requested an amendment to Certificate of Compliance (CoC) No. 9309, for the Model No. RAJ-II package. GNF-A identified non-critical dimensional errors in the currently approved drawings. This application provides revised drawings to correct the errors to reflect the as-built condition of the packagings. Based on the statements and representations in the application, the staff agrees that these changes do not affect the ability of the package to meet the requirements of 10 CFR Part 71.

**EVALUATION**

By application dated August 24, 2009, GNF-A provided revised drawings to correct non-critical dimensional errors in the currently approved drawings. Specific changes to the drawings include:

- Drawing No. 105E3738, Sheet 1  
No change to the drawing, however, the revision number was changed to Rev. 8
- Drawing No. 105E3738, Sheet 2  
The dimensions for the inner container Delrin guide were changed from 359 mm to 306 mm, and 284 mm to 283 mm, shown in Zones G5 and H5. The revision number was changed to Rev. 8. The basis for this change was to correctly match the dimensions of the Delrin guide (Item 30) in Zone F7, and reflect the as-built condition of the packagings currently in service.
- Drawing No. 105E3743  
The dimensions to the hole location on the end of the lid were changed from 255 mm to 225 mm, shown in Zone H2. The revision number was changed to Rev. 5. This change was required to match the fabrication drawings, and show appropriate dimensions for the lid to align with the outer container base, reflecting the as-built configuration of the packagings currently in service.
- Drawing No. 105E3744  
The spacing distance for the lid-lifting sling was corrected from 1550 mm to 1507 mm, in Zones I6 and I11. The revision number was changed to Rev. 6. This change corrected the dimension to match the fabrication drawings, and reflect the as-built condition of the packagings currently in service.

These minor changes to the drawings do not affect any critical dimensions, and will not impact the performance of the package design.

Because of the errors in the drawings referenced in CoC No. 9309, Rev. 8, this Certificate supersedes Rev. 8 in its entirety. However, staff recognizes the need for an orderly transition period between revisions of the CoC. As a result, staff has conditioned the Certificate to allow continued use of CoC 9309, Rev. 7, with reference to the revised drawings, for the same period of time as previously allowed under Rev. 8.

## **CONDITIONS**

The following changes have been made to the Certificate:

Condition No. 5(a)(3) Drawings, has been updated to reference the corrected drawings.

Condition No. 11, which authorized use of Revision 7 of the Certificate of Compliance until August 31, 2010, was revised by the addition of a reference to the corrected drawings.

## **CONCLUSION**

The Certificate has been revised to reference the revised drawings. These changes do not affect the ability of the package to meet the requirements of 10 CFR Part 71.

Issued with Certificate of Compliance No. 9309, Revision No. 9,  
on August 28, 2009.