

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER 9204	b. REVISION NUMBER 22	c. DOCKET NUMBER 71-9204	d. PACKAGE IDENTIFICATION NUMBER USA/9204/B(U)F-96	PAGE 1	PAGES OF 5
----	--------------------------------------	---------------------------------	------------------------------------	--	------------------	----------------------

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- a. ISSUED TO (*Name and Address*)
**EnergySolutions
2105 South Bascom Ave., Suite 230
Campbell, CA 95008**
- b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION
**EnergySolutions application dated January 24, 2011,
as supplemented.**

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

(a) Packaging

(1) Model No.: 10-160B

(2) Description

A cylindrical carbon steel and lead shielded shipping package, designed to transport radioactive waste material. The package is transported in the upright position and is equipped with steel encased, rigid polyurethane foam impact limiters on the top and bottom. The package has approximate dimensions, shielding, and weight as follows:

Package height	88 inches
Package outer diameter	78-1/2 inches
Package cavity height	77 inches
Package cavity diameter	68 inches
Overall package height, with impact limiters	130 inches
Overall package diameter, with impact limiters	102 inches
Lead shielding thickness	1-7/8 inches
Gross weight (packaging and contents)	72,000 lbs
Maximum total weight of contents, shoring, secondary containers, and optional shield insert	14,250 lbs

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9204	22	71-9204	USA/9204/B(U)F-96	2 OF	5

5.(a)(2) Description (Continued)

The packaging body consists of a 1-1/8-inch thick carbon steel (ASME SA516 or SA537) inner shell, a 1-7/8-inch thick lead gamma shield, and a 2-inch thick carbon steel outer shell (ASME SA516). The inner and outer shells are welded to a 5-1/2-inch thick carbon steel bottom plate. The packaging cavity has an optional 11-gage stainless steel liner. A 12-gage stainless steel thermal shield surrounds the cask outer shell in the region between the impact limiters. The impact limiters are secured to each other around the cask by eight ratchet binders.

The packaging lid is a 5-1/2-inch thick carbon steel plate, and has a 31-inch diameter opening equipped with a secondary lid. The primary lid is sealed with a double elastomer O-ring and 24 equally spaced 1-3/4-inch diameter bolts. The secondary lid is 46 inches in diameter, is centered within the primary lid, and is sealed to the primary lid by a double elastomer O-ring and 12 equally spaced 1-3/4-inch diameter bolts. The space between the double O-ring seals is provided with a test port for leak testing the primary and secondary lid seals.

The secondary lid is protected by a thermal shield which consists of two polished stainless steel plates separated by a thin air gap. The thermal shield is attached to the secondary lid lifting lugs with hitch-pins. The optional drain and vent ports are sealed with a plug and an O-ring seal.

The package is equipped with four tie-down lugs welded to the cask outer shell. Two lifting lugs and two redundant lifting lugs are removed during transport. The lid is equipped with three lifting lugs which are covered by the top impact limiter and rain cover during transport.

An optional shield insert may be used within the cask cavity for contents as specified in Condition No. 5(b)(1)(i) through (v). For contents specified in Condition No. 5(b)(1)(vi), a shield insert shall be used. Two shield insert designs are authorized for use: Shield Insert A and Shield Insert B. The shield inserts have side walls consisting of lead with a total thickness of 6.72 inches, located between an inner 8-inch SCH 40 steel pipe and an outer 24-inch SCH 60 steel pipe. The bottom consists of 6.0 inches of lead supported by a 0.75-inch thick steel base plate. The lid includes a steel encased lead plug (nominal lead thickness 8 5/8 inches), steel bolting plate, and flat elastomeric gasket. The main difference between the two is that Shield Insert B has no drain line at the bottom as Shield Insert A does.

(3) Drawings

The packaging is constructed and assembled in accordance with EnergySolutions Drawing No. C-110-D-29003-010, sheets 1 through 5, Rev. 16.

The Secondary Lid Thermal Shield is constructed in accordance with EnergySolutions Drawing No. DWG-CSK-12CV01-EG-0002-01, Rev. 3.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9204	22	71-9204	USA/9204/B(U)F-96	3 OF	5

Optional shield inserts are constructed in accordance with Drawing No. C-038-145083-004-01, Rev. 1, and C-038-145083-004-02, Rev. 1 (Shield Insert A) and Drawing No. DWG-LIN-201588-ME-0001-01, Rev. 0, and DWG-LIN-201588-ME-0001-02, Rev. 0 (Shield Insert B).

The Source Insert Steel Cribbing for shield inserts is constructed in accordance with EnergySolutions Drawing No. C-038-145083-005, Rev. 1.

5.(b) Contents

(1) Type and form of material

- (i) Byproduct, source, and special nuclear material, non-fissile or fissile-excepted, as special form, or non-special form in the form of process solids or resins, either dewatered, solid, or solidified waste, in secondary containers; or
- (ii) Dewatered, solid or solidified transuranic-containing wastes (TRU), fissile or non-fissile or fissile-excepted, in secondary containers; or
- (iii) Plutonium 239 (Pu-239) as Pu-Be neutron sources meeting the requirements of special form sources; or
- (iv) Neutron activated metals or metal oxides in solid form in secondary containers; or
- (v) Miscellaneous radioactive solid waste materials, including special form materials and powdered solids, in secondary containers.
- (vi) Byproduct material as Co-60 loaded using a shield insert.

(2) Maximum quantity of material per package

- (i) The maximum quantity of radioactive materials must be the lesser of the quantity determined by the methodology described in Attachment 1 to Chapter No. 7 of the application or 3000 A₂, except for contents specified in Condition No. 5(b)(1)(vi) for which the limit is 10,000 Ci of Co-60.
- (ii) Fissile contents must be limited to the fissile gram equivalent of 325 grams of Pu-239, as determined using the conversion factors in Table 9.1.3, in Chapter No. 4, Appendix 4.10.2, of the application. Plutonium content exceeding 0.74 TBq (20 Ci) must be in solid form.
- (iii) TRU exceeding the fissile limits of 10 CFR 71.15 must not be machine-compacted and must have no more than 1% by weight of special reflectors and no more than 25% by volume of hydrogenous material.
- (iv) Neutron sources as described in 5(b)(1)(iii) are limited to a maximum emission rate of 1.1E+8 n/sec.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9204	22	71-9204	USA/9204/B(U)F-96	4 OF	5

- (v) Maximum decay heat: 200 watts.
- (vi) Maximum weight of contents: 14,250 pounds including shoring, secondary containers, and either optional or mandatory shield insert. The contents of the shield insert shall have a maximum weight of 500 pounds.
- (vii) Explosives, corrosives, non-radioactive pyrophorics, and compressed gases are prohibited. Pyrophoric radionuclides may be present only in residual amounts less than 1 weight percent.
- (viii) The total amount of potentially volatile organic compounds present in the headspace of a secondary container is restricted to 500 parts per million.
- (ix) Powdered solid radioactive materials shall not include radioactive forms of combustible metal hydrides or combustible elemental metals, i.e., magnesium, titanium, sodium, potassium, lithium, zirconium, hafnium, calcium, zinc, plutonium, uranium, and thorium, or combustible non-metals, i.e., phosphorus.
- (x) Powdered solids contents with neutron emitters are not permitted.

5.(c) Criticality Safety Index 0.0

6. In addition to the requirements of Subpart G of 10 CFR Part 71:

- (a) The package must be prepared for shipment and operated in accordance with the Operating Procedures of Chapter No. 7 of the application. The shield inserts must be used according to Section 7.0 of Addendum A (for Shield Insert A), or Section 7.0 of Addendum B (for Shield Insert B).
- (b) Each packaging must meet the Acceptance Tests and Maintenance Program of Chapter No. 8 of the application. Shield inserts must meet the Acceptance Tests and Maintenance of Section 8.0 of Addendum A (for Shield Insert A), or Section 8.0 of Addendum B (for Shield Insert B).

7. Transport by air of fissile material is not authorized.

8. Flammable gas (hydrogen) concentration is limited to less than 5% in volume. For contents other than TRU waste, inerting is not allowed to limit the concentration of flammable gases. For TRU waste, compliance with the 5% hydrogen concentration limit is determined by the methods discussed in Appendix 4.10.2 of the application. For contents with a radioactivity concentration not exceeding that for Low Specific Activity material, the hydrogen concentration can be assumed to be less than 5% provided the package is shipped within 10 days of preparation, or within 10 days after venting of drums or other secondary containers.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9204	22	71-9204	USA/9204/B(U)F-96	5	OF 5


9. Payload containers authorized for shipment of TRU waste are the 30-gallon and the 55-gallon drums. TRU waste characteristics are determined and limited in accordance with Appendix 4.10.2 of the application.
10. The non-homogeneity of the package contents may lead to elevated levels of radiation on the package surfaces. Radiation surveys must be performed to obtain measurements from all surfaces of the package, and from the outer surfaces of the vehicle enclosure, unless process knowledge or survey history indicates that elevated radiation levels are not likely to be encountered.
11. Appropriate devices or measures must secure contents in the secondary container, if necessary.
12. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.
13. Shield Insert B shall be used only with dry-loaded contents.
14. Expiration date: October 31, 2020.

REFERENCES

EnergySolutions application dated January 24, 2011.

Supplements dated April 6, September 9, and October 28, 2011; July 20, July 26 and August 10, 2012; July 18, September 20, and November 4, 2013; and July 15, 2015.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION



Michele Sampson, Chief
Spent Fuel Licensing Branch
Division of Spent Fuel Management
Office of Nuclear Material Safety
and Safeguards

Date: August 14, 2015

SAFETY EVALUATION REPORT

Docket No. 71-9204
Model No. 10-160B Package
Certificate of Compliance No. 9204
Revision No. 22

SUMMARY

By letter dated July 15, 2015, *EnergySolutions* requested renewal of Certificate of Compliance No. 9204 for the Model No. 10-160B package. *EnergySolutions* did not request any changes to the design, operating procedures, acceptance tests, and maintenance program of the package. The Certificate has been renewed for a five year term.

EVALUATION

EnergySolutions requested renewal of Certificate of Compliance No. 9204 for the Model No. 10-160B package by letter dated July 15, 2015. No changes in the package design, operating procedures, acceptance tests and maintenance program or contents of the package were requested. The staff reviewed the documents referenced in the certificate of compliance, Revision No. 21, and determined that the required documentation was available and complete.

The following revisions to the certificate have been made:

Condition No. 14 was modified to change the expiration date of the certificate to October 31, 2020.

CONCLUSION

The certificate has been renewed for a five year term that expires on October 31, 2020. This change does not affect the ability of the package to meet the requirements of 10 CFR Part 71.

Issued with Certificate of Compliance No. 9204, Revision No. 22,
on August 14, 2015.