

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9360	1	71-9360	USA/9360/B(U)-96	1 OF	3

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- | | |
|--|--|
| a. ISSUED TO (<i>Name and Address</i>)
Industrial Nuclear Company, Inc.
14320 Wicks Blvd.
San Leandro, CA 94577 | b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION
Industrial Nuclear Company application
dated June 27, 2024. |
|--|--|

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5. (a) Packaging

(1) Model No.: Ten Hole Source Changer

(2) Description

The Model No. Ten Hole Source Changer package consists of ten titanium source tubes welded to a titanium hub which is encased in an enamel-coated depleted uranium (DU) gamma shield assembly. The DU gamma shield assembly is enclosed within a welded, 12-inch Schedule 10S stainless steel pipe, with overall dimensions of 12.75-inch diameter x 14.5-inch in height. A 0.25-inch thick stainless steel plate is welded to the bottom of the pipe and a 0.25-inch thick stainless steel mounting plate is welded to the inner surface of the pipe. The DU gamma shield assembly is laterally supported by eight short stainless steel channel sections that are welded to the inner wall of the pipe. The DU gamma shield assembly is also supported vertically by a 4-inch diameter Schedule 40S stainless steel pipe and a 1-inch diameter stainless steel bar that are welded to the inner surface of the bottom plate. Copper shim stock is installed between the DU-stainless steel interfaces to preclude a galvanic reaction between the two metals. The void space between the DU gamma shield assembly and the pipe shell is filled with rigid polyurethane foam which provides moisture protection for the DU gamma shield assembly. Ten lock box assemblies, which are located on top of the mounting plate, secure the special form capsules within the DU gamma shield assembly. A 0.375-inch closure lid is bolted to the package by eight 0.375-inch diameter bolts. Three stainless steel channels, which are positioned at 120 degrees intervals, are welded to the bottom plate exterior surface for supporting the package during transport. The maximum gross weight of the Model No. Ten Hole Source Changer package is 340 pounds.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9360	1	71-9360	USA/9360/B(U)-96	2 OF	3

(3) Drawings

The packaging is constructed in accordance with the following Industrial Nuclear Company Drawings: THSC-SAR-TA, Sheet 1 (Rev. 1); THSC-SAR-TA, Sheet 2 (Rev. 1); THSC-SAR-TA, Sheet 3 (Rev. 1); THSC-SAR-TA, Sheet 4 (Rev. 1); THSC-SAR-TA, Sheet 5 (Rev. 1); THSC-SAR-TA, Sheet 6 (Rev. 1); and THSC-SAR-TA, Sheet 7 (Rev. 1).

5. (b) Contents

(1) Type and form of material

Iridium-192 or selenium-75 as sealed sources that meet the requirements of special form radioactive material.

(2) Maximum quantity of material per package

Ten special form capsules. The maximum amount of material per capsule shall be 150 Ci (5.55 TBq).

Output curies are determined in accordance with American National Standard N432-1980, "Radiological Safety for the Design and Construction of Apparatus for Gamma Radiography."

(3) Maximum decay heat: 10.55 Watts

6. The sources shall be secured in the shielded position of the packaging by the source assembly lock box. The source assembly lock box must be fabricated of materials capable of resisting a 1475°F fire environment for one half-hour while maintaining its positioning function. The ball stop of the source assembly must engage the source assembly lock. The flexible cable of the source assembly and shipping plug must be of sufficient length and diameter to provide positive positioning of the source in the shielded position.

7. The name plate on the overpack must be fabricated of materials capable of resisting a 1475°F fire environment for one-half hour and maintain its legibility.

8. In addition to the requirements of Subpart G of 10 CFR Part 71:

(a) The package shall be prepared for shipment in accordance with the Operating Procedures of Chapter 7 of the application and

(b) Each package must meet the Acceptance Tests and Maintenance Program of Chapter 8 of the application.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9360	1	71-9360	USA/9360/B(U)-96	3 OF	3

9. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.
10. Expiration date: July 31, 2029.

REFERENCES

Industrial Nuclear Company application dated July 27, 2024.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION



Signed by Diaz-Sanabria, Yaira
on 07/29/24

Yaira Diaz-Sanabria, Chief
Storage and Transportation Licensing Branch
Division of Fuel Management
Office of Nuclear Material Safety
and Safeguards

Date: July 29, 2024





**UNITED STATES
NUCLEAR REGULATORY COMMISSION**
WASHINGTON, D.C. 20555-0001

**SAFETY EVALUATION REPORT
Docket No. 71-9360
Model No. Ten Hole Source Changer
Certificate of Compliance No. 9360
Revision No. 1**

SUMMARY

By application dated June 27, 2024 (Agencywide Documents Access and Management System [ADAMS] Accession No. ML24205A058), Industrial Nuclear Company, Inc. (INC) requested renewal of certificate of compliance (CoC) No. 9360, for the Model No. Ten Hole Source Changer. INC did not request any changes to the package design or its authorized contents. The certificate has been renewed for a 5-year term.

EVALUATION

The staff reviewed the documents referenced in the certificate and determined that the documentation was available in the ADAMS and complete.

CONDITIONS

The references section of the certificate was revised to include the date of the certificate renewal request.

CONCLUSION

The certificate has been renewed for a 5-year term, which expires on July 31, 2029. Based on the statements contained in the application, and the conditions listed above, the staff concludes that the changes indicated do not affect the ability of the package to meet the requirements of Title 10 of the *Code of Federal Regulations* Part 71.

Issued with CoC No. 9360, Revision No. 1.