NRC FORM 618 (8-2000) 10 CFR 71	U.S. NUCLEAR REGULATORY COMMISSION					IISSION
1. a. CERTIFICATE NUMBER 9371	b. REVISION NUMBER	c. docket number 71-9371	d. PACKAGES USA/9371/B(U)-96	PAGE 1	OF	PAGES 4
2. PREAMBLE						

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, *Code of Federal Regulations*, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.
- 3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION
 - a. ISSUED TO (Name and Address)
 QSA Global, Inc.
 40 North Avenue
 Burlington, MA 01803

b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION QSA Global, Inc., application dated April 25, 2018.

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

LEAR

- 5.
- (a) Packaging
 - (1) Model No.: 360
 - (2) Description

The Model No. 360 series of packages consist of a family of five package configurations used to transport Ir-192, Yb-169, and Se-75 source assemblies that meet the requirements for special form material. These five packages are the Model Nos. 360-2, 360-4, 360-4W, 360-10, and 360-10W. The external dimensions of all models are identical and are approximately: 15 inches [38 centimeters (cm)] long, 13.5 inches (34 cm) wide, and 15.9 inches (40 cm) tall.

GI

The major components of the package include: (i) the container assembly, (ii) the shield assembly, (iii) the shield retainer, (iv) the source securing assembly, (v) the cover assembly, and (vi) the source assemblies. Shielding is provided by either all tungsten or a combination of tungsten and depleted uranium shields. Models with the "W" designation use all tungsten shielding. An optional adapter tungsten shield can also be added to the top side of the Model No. 360 for additional shielding.

Depending on the source assembly to be transported, the source capsule will be attached to either a flexible steel wire or will be incorporated into a segment of a source chain. Each source securing mechanism incorporates a locking mechanism to secure the source inside the package and a source dust cap to further protect the end of the source assembly during transport. A lock assembly will secure the various lengths of the source assembles in the Model Nos. 360-2, 360-4, and 360-4W. Those models have

NRC F (8-2000) 10 CFR	ORM 618		U.S. NUCLEAR REGULATORY COMMISSION							
1 - 055										
1. a. CEF		9371		b. REVISION NUMBER	c. DOCKET NUMBER 71-9371	USA/9371/B(U)-96	PAGE 2	OF	PAGES 4	
10 CFR 1. a. CEF 5.	(a)	(2) (3) (3)	Descript the optic and 360 locking a The max maximul Model N 360-2 360-4 360-40 360-10 360-100 Drawing The pac Rev. G, The pac Rev. G, The pac C, sheet ents Type an Iridium-1 sources, All source steel wir	CERTIFICA FOR RADIOACT D. REVISION NUMBER 3 ion (continued) on of three loading -10W, chain asse assembly via stain kimum weight of the m package weight o. Package W 110 lbs. (50 130 lbs. (51 130 lbs. (51 130 lbs. (52) 155 lbs. (71 V 180 lbs. (82) s kage is constructed sheets 1-10. kage user should is 1-2. d form of material 192 (Ir-192), Seler which meet the r ce wire assemblie e or incorporated m quantity of material	TE OF COMPLINE IVE MATERIAL PA C. DOCKET NUMBER 71-9371 g positions: bottor mblies, which are he package varie ts are listed in the Veight 0 kg) 9 kg) 0.3 kg) 7 kg) 2 kg) ed in accordance reference QSA C hium-75 (Se-75), requirements of s s consist of the si into a segment of erial per package	ACKAGES d. PACKAGE IDENTIFICATION NUMBER USA/9371/B(U)-96 m, middle, or top. For the M e shorter in length, will be ser r extensions. s depending on the configure table below: with QSA Global, Inc., Drav Global, Inc., Drawing No. R3 and Ytterbium-159 (Yb-159 pecial form radioactive mat ource capsule attached to effa source chain.	PAGE 2 Aodel N ecured ration. wing No 360-Use erial. either a	OF os. 360 to the The o. R360 er, Rev ealed flexible	PAGES 4 D-10 D00, rision	
		(2)	Maximul The max Model N location	m quantity of mate kimum quantity of lo. 360 transporta of the package ar	erial per package Se-75 and Yb-16 tion package. Fo nd are listed in Ta	: 69 is 5,000 curies (Ci) for al r Ir-192, the values may de able 1 below.	l variatio	ons of n the	the	

NRC	FORM	618

(8-2000) 10 CFR 71 U.S. NUCLEAR REGULATORY COMMISSION

CERTIFICATE OF COMPLIANCE FOR RADIOACTIVE MATERIAL PACKAGES

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE		PAGES
9371	3	71-9371	USA/9371/B(U)-96	3	OF	4
9371	3	71-9371	USA/9371/B(U)-96		3	3 OF

5.

6.

(b) (2) Maximum quantity of material per package (continued):

_					
Model No.	Activity Shield Location	Maximum Package Capacity	Maximum Number of Sources		
360-2	Bottom	300 Ci	2		
	Top or Middle	270 Ci			
360-4	Bottom	600 Ci	4		
	Top of Middle	540 Ci			
360-4W	Any	260 Ci	4		
360-10	Any	1,500 Ci	10		
369-10W	Any	170 Ci	10		

Output curies for Ir-192 are determined by measuring the source output at 1 meter and expressing its activity in curies derived from the following: 0.48 R/(hr-Ci) (Ref: American National Standards Institute N432-1980, "Radiological Safety for the Design and Construction of Apparatus for Gamma Radiography").

(3) Maximum weight of contents:

0.3 lbs. (138 grams) for the Model No. 360-2 package.

0.6 lbs. (276 grams) for the Model Nos. 360-4 and 360-4W packages.

1.5 lbs. (690 grams) for the Model Nos. 360-10 and 360-10W packages.

The maximum content weight includes the mass of radioactive material and the source capsule handling wire assembly for a shipment containing the maximum number of source wire assemblies that can be transported in a package (i.e., 2 source assemblies for the Model No. 360-2, 4 source assemblies for the Model Nos. 360-4 and 360-4W packages, and 10 source assemblies for the Model Nos. 360-10 and 360-10W packages).

- (4) Maximum decay heat: 21 watts
- In addition to the requirements of Subpart G of 10 CFR Part 71:
 - (a) The package shall be prepared for shipment and operated in accordance with the Operating Procedures in Section No. 7 of the application;
 - (b) The package must meet the Acceptance Tests and Maintenance Program of Section No. 8.0 of the application.
- 7. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.

NRC FORM 618	and the second		U.S. NUCLEAR RE	GULATOR	YCOM	AISSION
(8-2000) 10 CFR 71						
1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE		PAGES
9371	3	71-9371	USA/9371/B(U)-96	4	OF	4
8. Revision No. 2 of this c	ertificate may be	used until Augus	t 31, 2020.			
9. Expiration date: Augus	t 31, 2023.					
		REFERENCES				
QSA Global, Inc., application d	ated April 25, 20	18.				. •
Date: $5/27/15$						



UNITED STATES NUCLEAR REGULATORY COMMISSION WASHINGTON, D.C. 20555-0001

SAFETY EVALUATION REPORT Docket No. 71-9371 Certificate of Compliance No. 9371 Revision No. 3

SUMMARY

By letter dated April 25, 2018, [Agencywide Documents Access and Management System (ADAMS) No. ML18149A025], QSA Global, Inc., (the applicant) requested the renewal of Certificate of Compliance (CoC) No. 9371 for the Model No. 360 series package. The applicant proposed editorial changes to the application and administrative changes related to the acquisition of NTP Radioisotopes (Europe) SA. The applicant did not request changes to the authorized contents in CoC No. 9371. Therefore, the applicant shall only transport the contents authorized as specified in the Model No. 360 series packages, CoC No. 9371, Revision 3. The certificate has been renewed for an additional five years.

EVALUATION

The applicant proposed administrative and editorial changes to the application ("Safety Analysis Report. QSA Global Inc., Models 360 Series, Type B(U)-96 Transport Package, April 2018, Revision 5") which are summarized in Attachment 3 of the letter dated April 25, 2018. The applicant submitted a consolidated application as part of this renewal request. The applicant noted that QSA Global, Inc. acquired assets and design authority for NTP Radioisotopes (Europe) SA, for which the applicant will be performing repairs and services of existing fuel assemblies as well as manufacturing of these assemblies under its United States (U.S.) Nuclear Regulatory Commission (NRC)- and International Standards Organization (ISO)- approved quality assurance programs. The certificate holder has a NRC-approved quality assurance program (Docket No. 71-0088).

QSA Global, Inc. added a few new source certificates to its application. The applicant did not request to modify the contents of CoC No. 9371. Therefore, the applicant is authorized to transport only the contents specified in the Model No. 360 series, CoC No. 9371, Revision 3.

The staff reviewed the proposed changes to the application and verified that previous changes to the application were incorporated into the consolidated application. The staff also made editorial changes to the CoC for clarity.

CONDITIONS

The following changes have been made to the certificate:

- 1. Condition No. 3(b) was revised to replace the date of the consolidated application to April 25, 2018.
- 2. Added condition No. 8, which authorizes use of the previous revision of the certificate for a period of one year.
 - "8. Revision No. 2 of this certificate may be used until August 31, 2020."
- 3. As a consequence of the inclusion of the new Condition No. 8, the previous Condition No. 8. was renumbered as No. 9 and condition No. 8. as condition No. 9. The expiration date of the CoC was revised as follows:
 - "9. Expiration date: August 31, 2023."
- 4. Revised the "REFERENCES" section to include the consolidated version of the application dated April 25, 2018, and deleted supplements, since these were incorporated into the 2018 consolidated application for the renewal request.

CONCLUSION

The certificate has been renewed for a five year term. These changes do not affect the ability of the package to meet the requirements of 10 CFR Part 71.

Issued with Certificate of Compliance No. 9371, Revision No. 3, on <u>8/27/18</u>.