



U.S. Department
of Transportation

Pipeline and
Hazardous Materials
Safety Administration

East Building, PHH-23
1200 New Jersey Ave, SE
Washington, D.C. 20590

**COMPETENT AUTHORITY CERTIFICATION FOR A
TYPE B(U)**

**RADIOACTIVE MATERIALS PACKAGE DESIGN
CERTIFICATE USA/0806/B(U) , REVISION 5**

**REVALIDATION OF CANADIAN COMPETENT AUTHORITY
CERTIFICATE CDN/2091/B(U)**

The Competent Authority of the United States certifies that the radioactive material package design described in this certificate satisfies the regulatory requirements for a Type B(U) package as prescribed in the regulations of the International Atomic Energy Agency¹ and the United States of America² The package design is approved for use within the United States for import and export shipments made in accordance with applicable international and domestic transport regulations.

1. Package Identification - Aspect 12K.
2. Package Description and Authorized Radioactive Contents - as described in Canadian Certificate of Competent Authority CDN/2091/B(U), Rev. 5 (attached).
3. General Conditions -
 - a. Each user of this certificate must have in his possession a copy of this certificate and all documents necessary to properly prepare the package for transportation. The user shall prepare the package for shipment in accordance with the documentation and applicable regulations.
 - b. Each user of this certificate, other than the original petitioner, shall register his identity in writing to the Office of Engineering and Research, (PHH-23), Pipeline and Hazardous Materials Safety Administration, U.S. Department of Transportation, Washington D.C. 20590-0001.

¹ "Regulations for the Safe Transport of Radioactive Material, 2018 Edition, No. SSR-6, Rev. 1" published by the International Atomic Energy Agency (IAEA), Vienna, Austria.

² Title 49, Code of Federal Regulations, Parts 100-199, United States of America.

CERTIFICATE USA/0806/B(U) , REVISION 5

c. This certificate does not relieve any consignor or carrier from compliance with any requirement of the Government of any country through or into which the package is to be transported.

d. Records of Management System activities required by Paragraph 306 of the IAEA regulations¹ shall be maintained and made available to the authorized officials for at least three years after the last shipment authorized by this certificate. Consignors in the United States exporting shipments under this certificate shall satisfy the applicable requirements of Subpart H of 10 CFR 71.

4. Special Conditions -

a. Maximum contents for each package configuration shall be as described and specified in Appendix 1 and Appendix 2. Radioactive contents shall have a valid special form radioactive material certificate.

5. Marking and Labeling - The package shall bear the marking USA/0806/B(U) in addition to other required markings and labeling.

6. Expiration Date - This certificate expires on November 30, 2029. Previous editions which have not reached their expiration date may continue to be used.

This certificate is issued in accordance with paragraph(s) 810 of the IAEA Regulations and Section 173.473 of Title 49 of the Code of Federal Regulations, in response to the December 2, 2025 petition by Source Production and Equipment Company, Inc., St. Rose, LA, and in consideration of other information on file in this Office.

Certified By:



William Quade
Acting Associate Administrator for
Hazardous Materials Safety

December 19, 2025
(DATE)

Revision 5 - Issued to revalidate Canadian Certificate of Approval
No. CDN/2091/B(U), Revision 5.



Certificate

CDN/2091/B(U) (Rev. 5)

Transport Package Design

The transport package design identified below is certified by the Canadian Nuclear Safety Commission pursuant to paragraph 21(1)(h) of the *Nuclear Safety and Control Act* and Subsection 10(1) of the *Packaging and Transport of Nuclear Substances Regulations*, 2015 and to the IAEA's *Regulations for the Safe Transport of Radioactive Material*, 2018 Edition.

REGISTRATION OF USE OF PACKAGES

All users of this authorization shall register their identity in writing with the Canadian Nuclear Safety Commission prior to the first use of this authorization and shall certify that they possess the instructions necessary for preparation of the package for shipment.

PACKAGE IDENTIFICATION

Designer: **SPEC150, LLC**
Make/Model: **ASPECT 12K (serial numbers 001 AS - 040 AS, XXX AS)**
Mode of Transport: **Air, Sea, Road, Rail**

IDENTIFICATION MARK

The package shall bear the competent authority identification mark "**CDN/2091/B(U)**".

PACKAGE DESCRIPTION

The ASPECT 12K transport package, as shown in drawing nos. B170100 (Rev. 7), B170101 (Rev. 5), B170210 (Rev. 5), and B170300 (Rev. 5) consists of cylindrical outer and inner containers.

The outer container includes a steel drum of 1.2 mm wall thickness and a Kaolite 1600 liner. The cover of the drum is secured by a clamp ring fastened by a bolt. Additionally, four tabs are welded to the underside of the cover and are engaged by M8 bolts through the side wall of the container. A plastic or wire tamper seal is attached to the clamp ring. Kaolite 1600 liners fill inside the drum, leaving a cavity inside the Kaolite to hold the inner container. The dimensions of the cavity are approximately 181 mm in diameter and 286 mm in height. A stainless steel or galvanized steel support cylinder separates the inner container from the Kaolite liner. A ceramic insulator or aluminum spacers may be used inside the cavity to keep the inner container in place.



The containment system consists of the sealed sources having a valid special form radioactive material certificate. The package contains one of three possible inner containers; maxiBulk, miniBulk, or 10-Channel. Each inner container consists of a stainless steel cylindrical shell and uses depleted uranium (DU) encased in stainless steel as shielding.

The miniBulk inner container is 140 mm in diameter, 180 mm in height with a cavity of 23.6 mm in diameter and 40 mm high, and weighs 37 kg including 31 kg of DU. The cavity inside the DU shield is lined with steel and the internal lid is closed with two M8 screws, while the external lid is closed with four M8 screws.

The maxiBulk inner container is 170 mm in diameter, 250 mm in height with a cavity of 31.6 mm in diameter and 72.5 mm high, and weighs 79 kg including 69 kg of DU. The cavity inside the DU shield is lined with steel and the internal lid is closed with two M8 screws, while the external lid is closed with four M8 screws.

The 10-Channel inner container is used as a source changer and is 180 mm in diameter, 280 mm high, and weighs 60 kg including 52 kg of DU. The DU shielding is made of two separate parts; the DU shield and the DU shield insert. There are ten channels in the DU to hold copper plated stainless steel source tubes. The special form sources, incorporated into source assemblies, are held in the tubes using hold down caps. The caps are covered by a lid held in place by an eyebolt.

An illustration of the package is shown on the attached ASPECT 12K descriptive assembly drawing.

Any modification to the package design must be submitted to the Canadian Nuclear Safety Commission for approval prior to implementation.

The configuration of the ASPECT 12K package with the maxiBulk inner container is as follows:

Shape:	Cylinder	Shielding:	Depleted Uranium
Mass:	149 kg	Outer Casing:	Steel
Length:	n/a	Height:	550 mm
Width:	n/a	Diameter:	390 mm

AUTHORIZED RADIOACTIVE CONTENTS

Appendix 1 and Appendix 2 list the maximum authorized radioactive contents that may be transported in each package configuration. All radioactive contents must have a valid special form radioactive material certificate.

MANAGEMENT SYSTEM

The management system for the design, manufacture, testing, documentation, use, maintenance and inspection of the package shall be in accordance with:

- SPEC150, LLC Document "Aspect Technology Ltd. Quality Assurance Program", Rev. 1*
- Packaging and Transport of Nuclear Substances Regulations, 2015
- *or latest current revision



SHIPMENT

The preparation for shipment of the package shall be in accordance with:

- SPEC150, LLC Document "ASPECT 12K Operating Manual", Rev. 6
- Packaging and Transport of Nuclear Substances Regulations, 2015

This certificate does not relieve the consignor from compliance with any requirement of the government of any country through or into which the package will be transported.

I. Tremblay
Designated Officer pursuant to paragraph 37(2)(a)
of the Nuclear Safety and Control Act



Appendix 1

The maxiBulk and miniBulk inner containers may contain one of the nuclear substances up to the corresponding maximum activity. The 10-Channel inner container may contain any of the nuclear substances as further specified in Appendix 2.

Isotope	maxiBulk	miniBulk	10-Channel
	Max Activity	Max Activity	Max Activity
	TBq	TBq	TBq
Iridium-192	350	112	56
Selenium-75	370	370	56
Ytterbium-169	56	56	56
Cesium-137	250	5.6	-



Appendix 2

The 10-Channel inner container can only hold the source assemblies listed in this Appendix and can hold up to 10 source assemblies each containing up to 5.6 TBq of Ir-192, Se-75 or Y-169.

Radiation Device	Source Holder	Drawing
GammaMat TSI Series	TI-GF7	H811.12-000
GammaMat TSI Series	TSI-GF7.8	H811.25-000
GammaMat SE/Rid- SE4P	SE-GM7	H811.30-000
GammaMat Hybrid	HY-GF7	Aspect 170233
Gilligan Eng. Viking	II-SA	CPPSII02A
Gilligan Eng. Viking V	V-SA	CPPSV02A
Gilligan Eng. Viking VI	VI-SA	CPPSVI02A
Gilligan Eng. Viking X	X-SA	CPPSX02A
Industrial Nuclear IR-100	32, 70400, C-376B, 87703, G-40T, G-40F	B912000
Sentinel 880 Series	A424-9, A424-25W, 91810, T-5, T-5F, C-337B, 7, 70200	D900000
Source Production SPEC-150	G-60, 969	B912000
Source Production SPEC-2T	G-1F, G-1T, G-3F	B912000



NOTES

Revision 0: November 19, 2014. New certificate.

Revision 1: November 27, 2014. Certificate amended to correct Appendix 2, Column 1, “Source Production Spec-15” and Source Production Spec 2-1” and replace with “Source Production SPEC-150” and “Source Production SPEC-2T”.

Revision 2: November 14, 2017. Certificate revised to increase the activity of Ir-192 and to change the interface between the depleted uranium and stainless steel.






Revision 3: November 8, 2019. Certificate renewed.

Revision 4: November 28, 2024. Certificate renewed. Co-60 removed from authorized contents.

On November 29, 2029: administrative change to correct the expiry date of the certificate.

Revision 5: November 28, 2025. Certificate revised to reflect issuance pursuant to the 2018 edition of the IAEA Regulations.

ASPECT 12K Descriptive assembly drawing / Dessin d'assemblage descriptif

		
<p><i>Figure 1.1: ASPECT 12K as presented for transport / tel que présenté pour le transport</i></p>	<p><i>Figure 1.2: ASPECT 12K with cover removed / avec le couvercle enlevé</i></p>	
		
<p><i>Figure 1.3: ASPECT 12K with inner maxiBulk container / avec conteneur intérieur maxiBulk</i></p>	<p><i>Figure 1.4: ASPECT 12K with inner miniBulk container / avec conteneur intérieur miniBulk</i></p>	<p><i>Figure 1.5: ASPECT 12K with inner 10-Channel container / avec conteneur interne à 10 canaux</i></p>



U.S. Department of
Transportation

**Pipeline and
Hazardous Materials
Safety Administration**

East Building, PHH-23
1200 New Jersey Ave, SE
Washington, D.C. 20590

CERTIFICATE NUMBER: USA/0806/B(U)-96

ORIGINAL REGISTRANT(S) :

Source Production and Equipment Company, Inc.
113 Teal Street
St. Rose, LA, 70087
USA

Industrial Nuclear Company, Inc.
14320 Wicks Blvd.
San Leandro, CA, 94577
USA

NRG
Westerduinweg 3
P.O. Box 25
1755 LE
PETTEN, North Holland,
NL

Isoflex Radioactive
108 Teal Street

St. Rose, LA, 70087
USA