



U.S. Department
of Transportation

Pipeline and
Hazardous Materials
Safety Administration

East Building, PHH-23
1200 New Jersey Ave, SE
Washington, D.C. 20590

**COMPETENT AUTHORITY CERTIFICATION FOR A
TYPE B(U)
RADIOACTIVE MATERIALS PACKAGE DESIGN
CERTIFICATE USA/9269/B(U) , REVISION 15**

The Competent Authority of the United States certifies that the radioactive material package design described in this certificate satisfies the regulatory requirements for a Type B(U) package as prescribed in the regulations of the International Atomic Energy Agency¹ and the United States of America² The package design is approved for use within the United States for import and export shipments made in accordance with applicable international and domestic transport regulations.

1. Package Identification - Model 650L Source Changer.
2. Package Description and Authorized Radioactive Contents - as described in U.S. Nuclear Regulatory Commission Certificate of Compliance No. 9269, Revision 14 (attached).
3. General Conditions -
 - a. Each user of this certificate must have in his possession a copy of this certificate and all documents necessary to properly prepare the package for transportation. The user shall prepare the package for shipment in accordance with the documentation and applicable regulations.
 - b. Each user of this certificate, other than the original petitioner, shall register his identity in writing to the Office of Engineering and Research, (PHH-23), Pipeline and Hazardous Materials Safety Administration, U.S. Department of Transportation, Washington D.C. 20590-0001.

¹ "Regulations for the Safe Transport of Radioactive Material, 2018 Edition, No. SSR-6, Revision 1" published by the International Atomic Energy Agency (IAEA), Vienna, Austria.

² Title 49, Code of Federal Regulations, Parts 100-199, United States of America.

CERTIFICATE USA/9269/B(U) , REVISION 15

c. This certificate does not relieve any consignor or carrier from compliance with any requirement of the Government of any country through or into which the package is to be transported.

d. Records of Management System activities required by Paragraph 306 of the IAEA regulations¹ shall be maintained and made available to the authorized officials for at least three years after the last shipment authorized by this certificate. Consignors in the United States exporting shipments under this certificate shall satisfy the applicable requirements of Subpart H of 10 CFR 71.

4. Special Conditions -

a. Aging Management protocols detailed in QSA Global In-Service Bulletin SB-25 dated December 2024 (attached) shall be followed.

5. Marking and Labeling - The package shall bear the marking USA/9269/B(U) in addition to other required markings and labeling.

6. Expiration Date - This certificate expires on November 30, 2030. Previous editions which have not reached their expiration date may continue to be used.

This certificate is issued in accordance with paragraph(s) 810 of the IAEA Regulations and Section 173.471 of Title 49 of the Code of Federal Regulations, in response to the July 30, 2025 petition by QSA Global, Inc., Burlington, MA, and in consideration of other information on file in this Office.

Certified By:



William Quade
Acting Associate Administrator for
Hazardous Materials Safety

August 25, 2025
(DATE)

Revision 15 - Issued to endorse U.S. Nuclear Regulatory Commission Certificate of Compliance No. 9269, Revision 14, to the Regulations for the Safe Transport of Radioactive Material, 2018 Edition, No. SSR-6, Rev. 1.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9269	14	71-9269	USA/9269/B(U)-96	1	OF 3

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- | | |
|---|--|
| a. ISSUED TO (Name and Address) | b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION |
| QSA Global, Inc.
40 North Avenue
Burlington, MA 01803 | QSA Global, Inc., consolidated application dated
October 9, 2024. |

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

(a) Packaging

- (1) Model No.: 650L
- (2) Description

A welded carbon or stainless steel cylindrical outer shell encases a welded carbon or stainless steel rectangular inner shell. The inner shell contains a titanium "U" tube set in depleted uranium along with internal supports. The tube is crimped in the middle of the "U" to provide a positive stop for the source assembly. Additional shielding is provided by lead or tungsten positioned at various locations around the depleted uranium shield. The Model No. 650L has two source locking assemblies, mounted on the top cover plate, that are used to secure the radioactive special form source, Iridium-192 or Selenium-75, in a shielded position during transport. The packaging measures approximately 10-inches (254 mm) wide, 13.25-inches (337 mm) high and 8.25-inches (210 mm) deep. The maximum weight of the packaging is 90 pounds (41 kg).

(3) Drawings

The packaging is constructed in accordance with QSA Global, Inc., Drawing No. R65006, Revision R, sheets 1-5.

(b) Contents

(1) Type and form of material

Iridium-192 as sealed sources which meet the requirements of special form radioactive material.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9269	14	71-9269	USA/9269/B(U)-96	2	OF 3

5.(b) Contents (continued)

Selenium-75 as sealed sources which meet the requirements of special form radioactive material.

(2) Maximum quantity of material per package

Ir-192: 240 curies (8.9 TBq) (output)

Se-75: 300 curies (11.1 TBq) (content)

Output curies are determined by measuring the source output at 1 meter and expressing its activity in curies derived from the following: 0.48 R/(h-Ci) Iridium-192 at 1 meter (Ref: American National Standard N432-1980, "Radiological Safety for the Design and Construction of Apparatus for Gamma Radiography").

(3) Maximum weight of contents

0.08 pounds (36 grams), including the mass of radioactive material and the weight of the source capsule handling wire assembly for a shipment containing two source wire assemblies.

(4) Maximum decay heat

Ir-192: 4.8 Watts

Se-75: 1.52 Watts

6. The source shall be secured in the shielded position of the packaging by the source assembly. The source assembly must be fabricated of materials capable of resisting a 1475°F fire environment for one-half hour and maintaining its positioning function. The cable of the source assembly must engage the source hold-down assembly. The flexible cable of the source assembly must be of sufficient length and diameter to provide positive positioning of the source at the crimp of the "U" tube.

7. The nameplates shall be fabricated of materials capable of resisting the fire test of 10 CFR Part 71 and maintaining their legibility.

8. In addition to the requirements of Subpart G of 10 CFR Part 71:

(a) The package shall be prepared for shipment in accordance with the Operating Procedures in Chapter 7 of the application, and

(b) The packaging shall be maintained in accordance with the Maintenance Program in Chapter 8 of the application.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9269	14	71-9269	USA/9269/B(U)-96	3	OF 3

9. Fabrication of new packagings is not authorized. Fabrication of replacement components needed to support shipment of existing packages is authorized, except for the depleted uranium shield and the inner carbon steel shell.
10. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.
11. Expiration date: November 30, 2030.

REFERENCES

QSA Global, Inc., consolidated application dated October 9, 2024.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

THOMAS BOYCE

Digitally signed by THOMAS
BOYCE

Date: 2025.02.19 18:18:01 -05'00'

Tom Boyce, Acting Chief
Storage and Transportation Licensing Branch
Division of Fuel Management
Office of Nuclear Material Safety
and Safeguards

Date: February 19, 2025

QSA GLOBAL

SERVICE BULLETIN

650L Extended Inspection & Maintenance for IAEA SSR-6: 2018 Compliance

Purpose

This document provides information applicable to the inspection and maintenance of the Model 650L transport package to comply with IAEA SSR-6 (2018). In addition to ensuring the package is in accordance with the operating instructions supplied with the transport package, per 10 CFR 71.87 and 71.89, specifically Sections 7 & 8 of the Model 650L Safety Analysis Report, compliance with this bulletin is required for all packages shipped under a USDOT certificate, or other foreign Type B certification, endorsed to IAEA SSR-6 (2018).

Package Inspection & Maintenance Requirements

The Model 650L packages must be maintained regularly by trained and qualified personnel to ensure the package complies with applicable Type B(U) or Type A approval requirements and the package maintains its integrity during transport.

The recommended inspection and maintenance requirements are based on the system's design, application, materials, anticipated work cycles, environmental factors of use under the normal and abnormal conditions of transport. A program of systematic maintenance will prolong the working life of the package in addition to ensuring safety during transport and use. Routine inspection of the package is required prior to each shipment. In addition, a complete annual servicing of the 650L package is necessary to ensure the package integrity.

Maintenance program administrators must recognize the need for maintenance intervals that are less than the required annual interval, especially in cases where the package is used in severe environmental conditions. Maintenance program administrators must ensure the systems are completely serviced immediately after observed damage or after exposure to severe conditions. Extreme or severe conditions may include, but is not limited to, conditions where the package was:

- Immersed in water or mud.
- Subjected to high-concentrations of particulate such as fly ash, sand or foundry green-sand.
- Subjected to hot radiography conditions.
- Subjected to salt-water conditions, caustic or acidic materials.
- Subjected to accidental drops or falling objects.
- Whenever subjected to extreme environmental conditions.

The complete, annual inspection and maintenance (also required after removal from long term storage – see Section 4) involves an enhanced inspection and service for package components and major assemblies.

Personnel performing the inspections and maintenance in this bulletin must be adequately trained and approved to perform these duties. Personnel approved and qualified under either a USNRC approved QA program or an ISO 9001 QA program to perform Type B container inspection and maintenance would meet the training requirements in this bulletin.

1. General Requirements

- a. The Model 650L transport package must be loaded and closed in accordance with procedures that, at a minimum, include the requirements in Sections 7 & 8 of the SAR and this bulletin. Shipment of Type B quantities of radioactive material are authorized for sources specified in Section 2. Maintenance and inspection of these packages is in accordance with the additional requirements specified in Section 3 and 4.

QSA GLOBAL

SERVICE BULLETIN

650L Extended Inspection & Maintenance for IAEA SSR-6: 2018 Compliance

NOTE: Package conformance after storage and prior to use for Type B shipments is ensured by proper inspection and maintenance. The materials used in the Model 650L packages are not vulnerable to degradation due to irradiation over time, and there will typically be no chemical/galvanic material interactions between package materials during storage so long as the package is not exposed to hazardous chemicals and is stored under controlled environmental conditions¹.

For packages removed from storage and prior to shipment, the package components are inspected for any degradation due to non-use/storage. Any degradation identified will prevent the package use for shipment until correction by replacement, service and/or repair. (Reference: IAEA SSR-6 §503(e) & 613A).

- b. Results of package annual inspections and maintenance covered in this bulletin must be recorded and include, at a minimum,
- The date of inspection and maintenance.
 - Name and signature of the qualified individual performing the required inspections.
 - Problems found and maintenance or repairs performed.
 - Package model number (e.g., 650L) and the serial number.
 - Associated equipment that was inspected and maintained.
 - Part numbers and associated lot numbers or serial numbers, when applicable, of replacement parts installed.

If any defective/damaged components are identified on the package or source(s) contained in the 650L, they must be removed from transport use and identified with a status indicator (tag, label, or tape) to prevent inadvertent shipment or use. Defective or damaged components must be repaired or replaced before continued use of the Model 650L package in transport.

NOTE: Repair of any 650L package must be performed by, or under the direction and approval of, QSA Global, Inc. only.

Contact QSA Global, Inc. if additional guidance or assistance is needed to determine actions to deal with defective/damaged 650L transport packages.

2. Authorized Package Contents

The Model 650L transport package is designed for use with a special form source capsules as approved under a U.S. Department of Transportation special form certification². The approved isotopes and maximum package activity limits are shown in Table A. Details of encapsulation as well as chemical and physical form of the radioactive material will comply with specifications approved under U.S. Department of Transportation or other Competent Authority special form certifications.

¹ Storage of the Model 650L packages should be in a temperature and humidity controlled area away from chemicals or other hazardous substances to prevent degradation of the package integrity while in storage.

² Special Form is defined in 10 CFR 71, 49 CFR 173, IAEA TS-R-1 and SSR-6.

QSA GLOBAL

SERVICE BULLETIN

650L Extended Inspection & Maintenance for IAEA SSR-6: 2018 Compliance

Table A: Isotopes Permitted in the Model 650L³

Isotope	Maximum Capacity ⁴	Maximum DU Weight	Maximum Package Weight
Ir-192	240 Ci	44 lbs (20 kg)	90 lbs (41 kg)
Se-75	300 Ci		

3. Packaging Maintenance and Inspection Prior to Shipment

- If the package has been in storage for 1 year or longer, inspection to the requirements in Section 4 must be completed in addition to the maintenance and inspection listed in this section.
- Ensure all markings are legible including the package serial number and that the labels are securely attached to the package. Labels should be easily legible at a distance of roughly 3 ft (1 m) and contain all necessary information.
- Inspect the package components for signs of damage or significant degradation. Ensure all welds are intact, the components are free of heavy rust and cracks/damage to the lid and container body, the lid and container flanges with no bends $\geq 20^\circ$ from normal. If there is any evidence of damage which could adversely impact the package integrity for Type B transport, contact QSA Global, Inc. prior to shipping.
- Assure all bolts, washers, nuts and fasteners (hardware) required for assembly of the package, and as specified on the drawings referenced on the Type B transport certificate, are fit for use. Except for the lid cover bolts and fasteners, do not disassemble any of the other package hardware to perform this inspection. Examine the visible external surfaces for any signs of damage including fatigue cracking.

Note: The hardware must be replaced if no longer fit for use (e.g., threads stripped, unable to fully thread, signs of cracking, galling, etc.). If replacement hardware is required, contact QSA Global, Inc. to obtain parts. This is necessary to ensure replacement hardware meets all applicable specifications listed on the drawings referenced on the Type B transport certificate.

- Ensure the locking assemblies allow free movement of the lock slide when performing an operational test and that the plunger lock engages and is functional. Ensure the shipping caps install and secure over the source tubes on the lock assemblies.
- Ensure the threaded holes used to secure the lid to the container body do not have damaged threads and engage the cover bolts. Threaded holes must not allow pass through without threading.
- Ensure the package can be assembled, including attachment of a seal wire as identified on drawing R65009 Revision R.

³ Sources allowed for transport in the 650L as Type B quantities limited to special form as defined in 10 CFR 71, 49 CFR 173, IAEA TS-R-1 and SSR-6.

⁴ Maximum Capacity Activity for Ir-192 is defined as output Curies as required in ANSI N432 and 10 CFR 34.20 and in line with TS-R-1/SSR-6 and Rulemaking by the USNRC and the USDOT published in the Federal Register on 26 January 2004.

QSA GLOBAL

SERVICE BULLETIN

650L Extended Inspection & Maintenance for IAEA SSR-6: 2018 Compliance

- h. If the 650L fails any of the inspections in steps 3.a-g, remove the package from use until it can be brought into compliance with the Type B certificate.

4. Packaging Annual Maintenance and Inspection

Model 650L packages must receive inspection and maintenance at least once a year. Annual maintenance and inspection must be performed by individuals specifically trained, qualified and authorized for this work.

NOTE: QSA Global, Inc. can perform annual inspection for customer owned 650Ls upon receiving a request for service.

To perform the annual maintenance/inspection, parts of the package must be disassembled and the major package sub-assemblies thoroughly cleaned and inspected to ensure the integrity of components that are critical to safety. These procedures can only be performed on an empty package, which requires transfer of the radioactive source assembly(ies) into an approved storage container.

A leak test of a sealed source must be performed every 6 months or prior to its first use after removal from storage. Acceptable results of a radio-assay must indicate removable contamination is less than <185 Bq (0.005 µCi). If the source requires a leak test, perform the test and obtain the results prior to transferring the source from the package into a source changer.

- a. If the package has not received an annual inspection per this section within the last year or the package has been in storage for 1 year or longer, inspection to the requirements in this section must be completed.
- b. Complete the inspections in Section 3.b through 3.h.
- c. Remove each lock assembly and disassemble. Replace all springs. Inspect all screws and fasteners (hardware) required for assembly of the lock assembly. Examine the screws and hardware visible external surfaces for any signs of damage including fatigue cracking.

Note: The hardware must be replaced if they are no longer fit for use (e.g., threads stripped, unable to fully thread, signs of cracking, galling, etc.). If replacement hardware or other lock assembly parts are required, contact QSA Global, Inc. to obtain parts. This is necessary to ensure replacement components meet all applicable specifications listed on the drawings referenced on the Type B transport certificate.

Reassembly both lock assemblies and attach them to the 650L container base. Ensure the locking assemblies allow free movement of the lock slide when performing an operational test and that the plunger lock engages and is functional. Install a safety wire to the lock assembly attachment screws as detailed on Sheet 3 of Drawing R65006 Rev R.

- d. If the package meets the requirements of 4 b. through c., complete an annual inspection sticker and apply one to the 650L top plate near the serial number stamping.
- e. Maintain records of this inspection and maintenance (see 1.b in this bulletin).



U.S. Department of
Transportation

**Pipeline and
Hazardous Materials
Safety Administration**

East Building, PHH-23
1200 New Jersey Ave, SE
Washington, D.C. 20590

CERTIFICATE NUMBER: USA/9269/B(U)-96

ORIGINAL REGISTRANT(S) :

QSA Global, Inc.
40 North Avenue
Burlington, MA, 01803
USA

Department of Energy
U.S. Department of Energy
1000 Independence Ave, SW
EM-60
Washington, DC, 20585
USA

Source Production and Equipment Company, Inc.
113 Teal Street
St. Rose, LA, 70087
USA

Industrial Nuclear Company, Inc.
14320 Wicks Blvd.
San Leandro, CA, 94577
USA

Bonded Inspections Incorporated
3840 Marquis Street
Garland, TX, 75042
USA

CIS-US (Pharmalucence)
10 DeAngelo Drive
Bedford, MA, 01730
USA

Department of the Navy
Naval Sea Systems Command
1333 Isaac Hull Ave. SE
Washington Navy Yard, DC, 20376-0001

USA

MISTRAS Holdings Group, CONAM Inspection & Engineering Services, Inc
899 Carol Court
Carol Stream, IL, 60188
USA

Western Industrial X-Ray
1707 Enterprise Drive
Unit J
P.O. Box 238
Fairfield, CA, 94533
USA

Calumet Testing Services, Inc.
1945 N. Griffith Blvd.
Griffith, IN, 46309
USA

Three Rivers Gamma Services
1132 Route 18 North
Burgettstown, PA, 15021
USA

Duke Energy Corporation
526 South Church Street
Charlotte, NC, 28202-1802
USA

International Inspection
10521 N. Lombard Street
Portland, OR, 97203
USA

Brazos Valley Inspection
P.O. Box 7717
Abilene, TX, 79608
USA

U.S. Non-Destructive Inspection
P.O. Box 7717
Abilene, TX, 79608
USA

Isoflex Radioactive
108 Teal Street

St. Rose, LA, 70087
USA

XCEL NDT
2755 State Highway 322
Longview, TX, 75603
USA

Industrial Inspection and Analysis
1110 Energy Drive
Abilene, TX, 79602
USA

Metalogic Inspection Services
6529 Cunningham Rd
Suite 2001
Houston, TX, 77041
United States

A2Z NDT (Non Destructive Testing)
3111 S. Valley View Blvd
Suite Z-105
Las Vegas, NV, 89102
USA

SummitNDE
8762 Louisiana Street
Suite R
Merrillville, IN, 46410
USA