



U.S. Department
of Transportation

Pipeline and
Hazardous Materials
Safety Administration

East Building, PHH-23
1200 New Jersey Ave, SE
Washington, D.C. 20590

**COMPETENT AUTHORITY CERTIFICATION FOR A
TYPE FISSILE
RADIOACTIVE MATERIALS PACKAGE DESIGN
CERTIFICATE USA/9294/AF-96, REVISION 12**

The Competent Authority of the United States certifies that the radioactive material package design described in this certificate satisfies the regulatory requirements for a Type AF package for fissile material as prescribed in the regulations of the International Atomic Energy Agency¹ and the United States of America² The package design is approved for use within the United States for import and export shipments made in accordance with applicable international and domestic transport regulations.

1. Package Identification - Global Nuclear Fuels Model No. NPC.
2. Package Description and Authorized Radioactive Contents - as described in U.S. Nuclear Regulatory Commission Certificate of Compliance No. 9294, Revision 10 (attached).
3. Criticality - The minimum criticality safety index is 0.7. The maximum number of packages per conveyance is determined in accordance with Table 11 of the IAEA regulations cited in this certificate.
4. General Conditions -
 - a. Each user of this certificate must have in his possession a copy of this certificate and all documents necessary to properly prepare the package for transportation. The user shall prepare the package for shipment in accordance with the documentation and applicable regulations.
 - b. Each user of this certificate, other than the original petitioner, shall register his identity in writing to the Office of Engineering and Research, (PHH-23), Pipeline and Hazardous

¹ "Regulations for the Safe Transport of Radioactive Material, 2012 Edition, No. SSR-6" published by the International Atomic Energy Agency (IAEA), Vienna, Austria.

² Title 49, Code of Federal Regulations, Parts 100-199, United States of America.

CERTIFICATE USA/9294/AF-96, REVISION 12

Materials Safety Administration, U.S. Department of
Transportation, Washington D.C. 20590-0001.

- c. This certificate does not relieve any consignor or carrier from compliance with any requirement of the Government of any country through or into which the package is to be transported.
- d. Records of Management System activities required by Paragraph 306 of the IAEA regulations¹ shall be maintained and made available to the authorized officials for at least three years after the last shipment authorized by this certificate. Consignors in the United States exporting shipments under this certificate shall satisfy the applicable requirements of Subpart H of 10 CFR 71.

5. Special Conditions -

- a. The package must be prepared for shipment and operated in accordance with the Operating Procedures found in Chapter 7 of the safety analysis report, as supplemented. Within each inner containment canister assembly (ICCA), the contents and secondary packaging (i.e. dunnage) must provide a snug fit.
- b. Each packaging must be acceptance tested and maintained in accordance with the Acceptance Tests and Maintenance Program in Chapter 8 of the safety analysis report.
- c. Transport by air of fissile material is not authorized.

6. Marking and Labeling - The package shall bear the marking USA/9294/AF-96 in addition to other required markings and labeling.

7. Expiration Date - This certificate expires on November 30, 2030. USA/9294/AF-96 Revision 11 may be used until November 30, 2025. All other revisions are not authorized for use.

CERTIFICATE USA/9294/AF-96, REVISION 12

This certificate is issued in accordance with paragraph(s) 816 of the IAEA Regulations and Section 173.471 and 173.472 of Title 49 of the Code of Federal Regulations, in response to the March 21, 2025 petition by Global Nuclear Fuels - Americas, Wilmington, NC, and in consideration of other information on file in this Office.

Certified By:



 William Schoonover
Associate Administrator for Hazardous
Materials Safety

March 25, 2025

(DATE)

Revision 12 - Issued to endorse U.S. Nuclear Regulatory Commission
Certificate of Compliance No. 9294, Revision 10.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9294	10	71-9294	USA/9294/AF-96	1 OF	4

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- a. ISSUED TO (*Name and Address*)
- b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION

Global Nuclear Fuel - Americas, LLC
P.O. Box 780
Wilmington, NC 28402

NPC Safety Analysis Report, application dated
December 12, 2019, as supplemented

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.(a) Packaging

- (1) Model No.: NPC
- (2) Description

A cubic stainless steel and foam outer packaging with nine cylindrical containment vessels for the transport of type A quantities of low-enriched uranium oxide powder, pellets, and compounds of uranium as defined in 5(b). The overall package dimensions are approximately 45 inches wide, 45 inches deep, and 44 inches high.

The outer packaging consists of a 10-gage stainless steel outer shell with a ceramic fiber board liner and rigid polyurethane foam filler. The foam filler has a three-by-three array of vertical cylindrical cutouts that accommodate stainless steel sleeves for placement of the containment vessels. The outer packaging is equipped with a top cover that is secured to the outer packaging body by a combination of 16 closure cap screws and four closure strips secured by 24 bolts.

The containment vessel is a maximum 8.515 inches in inner diameter and approximately 32 inches in overall length. The containment vessel is constructed of 18-gage stainless steel, surrounded by a cadmium sheet and polyethylene wrap within a 24-gage stainless steel jacket. The containment vessel is closed by a 16-gage closure lid, a silicone rubber gasket, and a band clamp assembly, which is composed of a 0.063-inch thick strap and retainer, a T-bolt, and a nut.

The gross weight of the package (packaging and contents) is 1,302 kg (2,870 pounds). The maximum weight of the contents is 540 kg (1,190 pounds).

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9294	10	71-9294	USA/9294/AF-96	2 OF	4

5.(a) (3) Drawings

The packaging is fabricated and assembled in accordance with the following Global Nuclear Fuel - Americas, LLC, Drawing Nos.:

177D4970, Sheet 1, Revision 1
177D4970, Sheet 2, Revision 0
177D4970, Sheet 3, Revision 0
177D4970, Sheet 4, Revision 0
177D4970, Sheet 5, Revision 0
177D4970, Sheet 6, Revision 0
177D4970, Sheet 7, Revision 0
177D4970, Sheet 8, Revision 1
SK105E4037, Sheet 2, Revision 1

(b) Contents

Table 1: Type, Form, and Maximum Quantity of Material Per Package

Material Form (≤5.00 wt.% U-235)	Particle Size Restriction: Minimum OD (Inches)	Maximum Loading per ICCA (kgs)		Maximum Loading per NPC (kgs)	
		Net	Uranium	Net	Uranium
Homogenous Uranium Compounds	N/A	60.0	52.89	540.0	476.1
Heterogenous UO ₂ Pellets (BWR)	0.342	60.0	48.48	540.0	436.3
Heterogenous UO ₂ Pellets(PWR)	0.300	60.0	46.71	540.0	420.4
Heterogenous Uranium Compounds	Unrestricted particle size	60.0	40.54	540.0	364.8

The "Material Form Column" must comply with the following constraints:

- Neither solutions, free liquids, uranium metal nor uranium metal alloys are authorized and shall not be present. Homogenous and heterogenous uranium compounds may be mixed with other non-fissionable diluent materials (e.g., sand, iron, iron hydroxide, silica, carbon from ash, etc.) except for deuterium, tritium and beryllium.
- The solid form material within any individual NPC must be the same.
- Homogeneous and heterogeneous uranium materials are limited to solid form.
- For purposes of determining if the homogenous or heterogeneous criteria apply: if the particle size distribution is such that a majority of the particles are 1730 μm or greater, then the heterogenous payload criteria of Table 1 applies. If a majority of the particle size distribution is below 1730 μm, the homogenous payload criteria of Table 1 apply.
- The maximum mass of any Inner Containment Canister Assembly (ICCA) inner packaging materials (e.g., plastic bags or bottles) is unrestricted provided the mean hydrogen atom density of the packaging materials to be shipped inside the inner volume of each ICCA is not greater than water.

CERTIFICATE OF COMPLIANCE FOR RADIOACTIVE MATERIAL PACKAGES

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9294	10	71-9294	USA/9294/AF-96	3	OF 4

- Authorized materials also include UO_2 pellets present in standard PWR and BWR reactor fuel assembly lattice designs (e.g., 17X17 PWR fuel assemblies, 10X10, 9X9, 8X8 BWR fuel assemblies).
- The payload within an NPC may be distributed in any ratio within the nine ICCAs, provided that the Maximum Loading per ICCA and the Maximum Loading per NPC requirements of Table 1 are met. The payload within an ICCA can be enclosed in plastic poly bottle receptacles (e.g., bags, poly bottles, etc.).
- The "Material Form Column" homogeneous and heterogeneous uranium compounds are dry solids resulting from scrap recovery and waste incineration processes. Example compounds include:

- | | |
|---|---|
| <ul style="list-style-type: none"> • uranium oxides (UO_2, U_3O_8, or UO_x $x > 2$) • uranyl nitrate (UN, $\text{UO}_2(\text{NO}_3)_2$) • uranyl nitrate hexahydrate (UNH, $\text{UO}_2(\text{NO}_3)_2 \cdot 6\text{H}_2\text{O}$) • uranium tetrafluoride (UF_4) • sodium uranate (Na_2UO_4) • sodium diuranate ($\text{Na}_2\text{U}_2\text{O}_7$) • sodium diuranate hexahydrate ($\text{Na}_2\text{U}_2\text{O}_7 \cdot 6\text{H}_2\text{O}$) • ammonium diuranate (ADU, $3\text{UO}_3 \cdot 2\text{NH}_3 \cdot 4\text{H}_2\text{O}$) • ammonium uranyl carbonate (AUC, $(\text{NH}_4)_4\text{UO}_2(\text{CO}_3)_3$) | <ul style="list-style-type: none"> • dried calcium (Ca) uranium compounds/mixtures/sludges/ash, (e.g., CaUO_3, CaUO_4, Ca_2UO_5, Ca_2UO_4, Ca_3UO_6, $\text{CaU}_3\text{O}_{10} \cdot 4\text{H}_2\text{O}$, $\text{CaU}_6\text{O}_{19} \cdot 11\text{H}_2\text{O}$ and $\text{CaU}_6\text{O}_{19} \cdot 10\text{H}_2\text{O}$) • dried sodium (Na) uranium compounds/mixtures/sludges/ash, (e.g., $\text{Na}_2\text{U}_2\text{O}_7 \cdot 3\text{H}_2\text{O}$ and $\text{Na}_2\text{U}_2\text{O}_7 \cdot \text{H}_2\text{O}$) • dried iron (Fe) uranium compounds/mixtures/sludges/ash |
|---|---|

5.(c) Criticality Safety Index 0.7

6. In addition to the requirements of Subpart G of 10 CFR Part 71:

- The package must be prepared for shipment and operated in accordance with the Operating Procedures in Chapter 7 of the application, as supplemented. Within each ICCA, the contents and secondary packaging (i.e., dunnage) must provide a snug fit.
- Each packaging must be acceptance tested and maintained in accordance with the Acceptance Tests and Maintenance Program in Chapter 8 of the application.

7. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.

8. Transport by air of fissile material is not authorized.

9. Revision No. 9 of this certificate may be used until November 30, 2025.

10. Expiration date: November 30, 2030.


**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9294	10	71-9294	USA/9294/AF-96	4 OF	4

REFERENCES

NPC Safety Analysis Report, Application dated December 12, 2019

FOR THE U.S. NUCLEAR REGULATORY COMMISSION



Signed by Diaz-Sanabria, Yaira
on 03/19/25

Yaira Diaz-Sanabria, Chief
Storage and Transportation Licensing Branch
Division of Fuel Management
Office of Nuclear Material Safety
and Safeguards

Date: March 19, 2025





U.S. Department of
Transportation

**Pipeline and
Hazardous Materials
Safety Administration**

East Building, PHH-23
1200 New Jersey Ave, SE
Washington, D.C. 20590

CERTIFICATE NUMBER: USA/9294/AF-96

ORIGINAL REGISTRANT(S) :

Global Nuclear Fuels - Americas
3901 Castle Hayne Road
Mail Code K-84
Wilmington, NC, 28401
USA

Westinghouse
Westinghouse Electric Company - Nuclear Fuel
Columbia Fuel Fabrication Facility
5801 Bluff Road
Hopkins, SC, 29061
USA

Framatome Inc.
2101 Horn Rapids Road
Richland, WA, 99354
USA